



## technical specifications HSK-RA 75

width (mm)	925 (782)
length (mm)	1467 (1200)
height (mm)	1426 (1232)
width with cover panel (mm)	890
length with cover panel (mm)	1335
height with cover panel (mm)	1536
water content (l)	280
weight (kg)	1300
heating surface (m <sup>2</sup> )	8,10
heating output (kW)	0-75
rated heat output (kW)	75
CO <sup>2</sup> (%)	10,00
efficiency (%)	>90
flue gas mass flow (kg/Sek.)	0.067000
flue gas temperature (°C)	180
flue depress (Pa)	25
flue depress with fgb (Pa)	15
flue depress with underpressure control (Pa)	10
pressure drop at dT 10K (mbar)	15,90
max. pressure (bar)	3
heat flow (Zoll)	1 1/2
heat return (Zoll)	1 1/2
safety flow (Zoll)	1
safety return (Zoll)	1
filling and draining (Zoll)	1/2
safety cooling inlet (Zoll)	1
safety cooling outlet (Zoll)	1
sensor safety valve (Zoll)	1/2
flue gas pipe Ø (mm)	200
min. opening for air supply (cm <sup>2</sup> )	200
power supply	400V/16A 5polig
min. volume flow rate for return flow boot at 15K (m <sup>3</sup> /h)	1,43

technical specifications HSK-RA 75

Fa. Heizomat GmbH - Gerätebau / Energiesysteme - 91710 Gunzenhausen - OT Maicha 21 - 09836/9797-0

The right to any changes as may be technically or legally required is reserved.