



the right to any changes as
 may be technically or legally
 required is reserved.

technical specifications RHK-AK 155

width (mm)	930 (942)
length (mm)	2382
height (mm)	2000 (1950)
width with cover panel (mm)	1152
length with cover panel (mm)	2194
height with cover panel (mm)	2011
water content (l)	510
weight (kg)	2320
heating surface (m ²)	13,10
heating output (kW)	0-149
rated heat output (kW)	149
CO ² (%)	10,00
efficiency (%)	>90
flue gas mass flow (kg/Sek.)	0.132000
flue gas temperature (°C)	180
flue depress (Pa)	-
flue depress with fgb (Pa)	18
flue depress with underpressure control (Pa)	10
pressure drop at dT 10K (mbar)	86,20
max. pressure (bar)	3
heat flow (DN)	80
heat return (DN)	80
safety flow (Zoll)	1 1/2
safety return (Zoll)	1 1/2
filling and draining (Zoll)	1 1/4
safety cooling inlet (Zoll)	-
safety cooling outlet (Zoll)	-
sensor safety valve (Zoll)	-
flue gas pipe Ø (mm)	300
min. opening for air supply (cm ²)	350
power supply	400V/16A 5polig
min. volume flow rate for return flow boot at 15K (m ³ /h)	2,87

technical specifications RHK-AK 155

Stand 29.04.2011

Fa. Heizomat GmbH - Gerätebau / Energiesysteme - 97110 Gunzenhausen - OT Maicha 21 - 09836/9797-0